

# CLF                      LF-128

## MANUAL OF LF-128 RIVETING MACHINE



**JMA**  
JIM'S MACHINES & ACCESSORIES

### SPECIFICATIONS: (Pneumatic Type)

AC 3 Phase	<input checked="" type="checkbox"/> 220V <input type="checkbox"/> 380V <input type="checkbox"/> Option V	<input type="checkbox"/> 50 Hz <input type="checkbox"/> 60 Hz
Stroke of Spin Head	20-40 mm	
Riveting Capacity (Mild Steel Rivet)	(Solid rivet): 2 - 5 mm (Dia.) (Hollow rivet): 2 - 9 mm (Dia.)	
Distance between Punch and Table	70- 190 mm	
Depth of Throat	125 mm	
Working Table (LxW)	342x182 mm	
AC Motor Rating 4 Pole	1/2 Hp	
Gauge Pressure	2 - 7 kgf/cm <sup>2</sup>	
Max. Output	720 Kgf	
Working Cycle Time	0.5 - 6 Second.	
N.W.	134 Kgs	
G.W.	175 Kgs	
Dimension (L*W*H)	560x400x1155 mm	
Wooden case (L*W*H)	650x490x1315 mm	
<p>■ Specifications and designs are subject to change without notice.</p>		

Call: +61(0)414646212 email: info@jimsmachines.com.au